

AXON[®] connect UPS



Improving the safety
of your underground
environment

- > Enables plug-and-play voice solution
- > Fit for purpose
- > Provides space for the Voice Headend PC
- > Combined power 240W
- > 12 hours of operation time with the intended load



AXON

connect UPS

MST Global's AXON connect UPS is a mid-level uninterruptible power supply offering reliability and peace of mind for hard rock mines and tunnels.

The primary purpose of the AXON connect UPS is to enable voice and other IP solutions for the tunneling and hard rock mining environments in a reliable and cost-effective manner. AXON connect serves as both, the PoE injector and the network junction device for a number of daisy chained PoE clients such as Wi-Fi access points. It also provides space and power supply for an optional industrial PC that can be placed inside the enclosure.

SPECIFICATIONS

AC Input

- > 110-240 AC Single Phase

Output Connectors

- > 2 channels, RJ45, IP65 rated
- > 20mm cable gland for optional connections

DC Output Power

- > PoE, 56 Volt DC, 2A (combined)
- > Internally available power for industrial PC: 24V, 6A

External Indicators

- > Battery Discharge
- > Battery Fail
- > DC OK

Working Temperature & Humidity

- > -20°C to +80°C
- > 20 ~ 90% RH

Battery Configuration

- > 24 Volt, 33AH Batteries

Battery Type & Terminal Style

- > Battery: Deep Cycle AGM
- > Terminal: T5/8mm stud

Battery Protection

- > Battery low protection
- > Battery reverse polarity fuse

Internal Electrical Installation

- > DIN rail TS35/7.5 or 15 terminal blocks

Electrical Components

- > All components EMC compliant
- > All components RoHS compliant

IP Connectivity

- > IP traffic is passed from one output connector to the other

Internal Space Usage

- > Space for Voice Head End Server

Enclosure

- > Material: Powder coated steel
- > Ingress Protection: IP65

Dimensions (mm)

- > 700(h) x 500(w) x 250(d)

Weight

- > ~40kg

Product Ordering Code

- > Connect UPS 33AH W-AXON-C-33AH-K